

# Micro-Hydro-Power-Vertical-Tubular-Turbine- GD-LZ-20-8KW



<b>Main Specifications</b>		
<b>Turbine</b>		Remarks
Type	GD-LZ-20-8KW	Vertical Tubular Turbine
Rated Head	9m	
Rated Flow	161 l/s	
Power	8 KW	
Efficiency	60%	
<b>Generator</b>		Remarks
Type	SF8-4	Conforms to the IEC international electrician committee standard & CE standard
Rated Power	8KW	
Rated Voltage	230V	
Rated Current	34.78 A	
<b>Frequency</b>	50Hz	
Rated Rotational	1500r/min	
Phase	1	
P.F.	0.9	
Elevation	≤3000m	
Insulation Grade	B/B	
Protection Grade	IP44	

Ambient Temperature	-25°C ~ +50°C			
Relative Humidity	≤90%			
<b>Control Panel</b>				<b>Remarks</b>
Safety Protection	Short circuit Protection			
	Islanding Protection			
	Over Load Protection			
	Grounding Fault Protection			
Packing Material	Fiberboard			
Packing Size	1.5 M3			
Packing Weight	Net	Kg	520	
	Gross	Kg	560	
Stated: This product presents or the technical parameter revision is the technical improvement result, no other explanation.				